

Sump Cleaners

REMOVE CHIPS, SLUDGE & SOLIDS WITH MINIMAL DOWNTIME



Eriez Sump Cleaners

Eriez Sump Cleaners rapidly remove fluid, sludge and chips from the sump, filter the sludge and chips from the fluid via the reusable integral filter liner, and return the filtered fluid to the sump. A polypropylene filter sleeve filters to a nominal 50 microns. For finer filtration, a single-use paper filter sleeve (to 20 microns nominal) can be inserted into the chip basket.

In just ten to fifteen minutes, a CNC machine tool sump with 50 gallons of coolant and 20 pounds of sludge can be completely cleaned and the filtered coolant returned to the sump.

Features

- Power sources: LP gas, electric or air
- Capacities ranging from 50 to 1,000 US gallons
- Single and twin tank units with capacities of up to 500 gallons each
- Push-around configurations with center mounted wheels and casters
- Everything self contained for easy portability
- Towable units include end mount casters and tow bar



Machine tool coolant, chips and sludge are easily vacuumed out of the sump.



Sump Cleaner Operation

Dirty Coolant

Powerful suction removes heavy solids, chips and sludge from any machine tool sump at a rate up to 100 GPM



Chip Basket

Heavy-duty perforated chip basket is removed via crane. Various basket liners can further filter coolants to 20 microns



The reusable polypropylene filter sleeve is inserted into the chip basket to filter coolant to 50 microns. Finer filtration of 20 microns nominal can be achieved with a single use paper filter sleeve.

Power Options

Electric, Liquid Propane Gas and Air powered models available for different environments

Filtered Coolant

Clean filtered coolant is immediately pumped back into the sump



Once filtered, coolant is returned to the sump at a rate of 20 to 40 GPM.

TSUBAKI AUTOMOTIVE

“The Eriez Sump Cleaner literally paid for itself in the first use.”

“With the Eriez Sump Cleaner, it now takes two hours to do the complete job, where it used to take 8 to 11 hours per machine. We re-use the filtered oil at least one time over, which saves us 50 percent on oil consumption. We save almost \$70,000 per year in cutting oil alone. Add in labor savings and reduction in downtime and the total payback is over \$150,000 per year.”

Sump Cleaners

Eriez offers the widest assortment of sump cleaners to keep machine tools operating at peak performance, with capacities to 1,000 gallons and three power options.

Tank capacities:

Single tank units - 100, 175, 300, 400, 500, 1000 gallons

Twin tank units - 50/50, 100/100, 150/150, 200/200, 300/300, 400/400, 500/500 gallons

Features

- 3.5 cubic foot chip basket in 100 gallon units and 5.3 cubic foot chip basket for 175 gallon and larger units. Both with 800 pound capacity and hinged trap door bottom
- Two reusable polyfiber sleeves for chip basket
- 20' long 2" diameter suction and 1-1/2" diameter discharge hoses
- Heavy duty tank with 14" easy on/off manhole cleanout on end of tank. Easy lift chip basket lid.
- Push-around configuration, including center mounted 12" x 3" wheels and 4" x 2" casters mounted on each end, plus forklift brackets
- One 3' x 2" cleaning tool



Chip basket captures chips and sludge from dirty coolant during cleaning.



Easy access to the discharge hose connection.

Electric Sump Cleaner

120 volt single phase unit

These sump cleaners utilize a 120-volt motor assembly that generates 10" HG vacuum with suction rates up to 85 GPM while being able to pick up chips, sludge, grinding swarf and other solids. A discharge pressure of 5 PSI for discharge rates up to 40 GPM.

3 Phase (208, 240, 480, 575 volt) units

Utilize cast iron 3MP positive displacement blower coupled to a 5 HP motor that generates 12-15" HG vacuum power with suction rates up to 100 GPM while being able to pick up chips, sludge, grinding swarf and other solids. A discharge pressure of 5-7 PSI for discharge rates up to 40 GPM.



LP Gas Driven Cleaner

The LP Gas (Liquefied Petroleum Gas) powered Sump Cleaner utilizes a cast iron 3MP positive displacement blower coupled to a 25 HP electric start LP gas engine that generates 12-15" HG vacuum power with suction rates up to 100 GPM while being able to pick up chips, sludge, grinding swarf, etc. Discharge pressure of 5-7 PSI for discharge rates up to 40 GPM.



Air Venturi Sump Cleaner

An Air Venturi vacuum generator creates vacuum levels up to 13" HG for suction rates up to 110 GPM while being able to pick up chips, sludge, grinding swarf and other solids. A pre-set air pressure regulator for discharge is set for 5-7 PSI, with tank depressurization valve for discharge rates up to 40 GPM.



Note: Air Venturi requires a 1/2" ID air line.

Twin Compartment Sump Cleaner

Eriez Twin Compartment Sump Cleaners have one tank for dirty fluid and one for new or recycled fluid.

The operator fills the clean side with new or recycled fluid, goes to the machine tool sump, and pumps out the dirty fluid, solids and chips into the dirty side of the unit. The operator then refills the machine tool sump with the clean fluid from the clean side of the sump cleaner.

The sump cleaner is then used to transport the dirty coolant to an Eriez Coolant Recycling System for further processing or to a coolant disposal tank. Twin tank option is available with all power supplies.



50 Gallon Sump Cleaner

120 volt 3 stage motor assembly that generates 10" HG vacuum with suction rates up to 85 GPM while being able to pick up chips, sludge, grinding swarf and other solids. A discharge pressure of 5 PSI for discharge rates up to 40 GPM.

Features

- Electric switch to shut off motor when unit is full
- 10' long x 2" ID suction and 1-1/2" discharge hoses
- 1.6 cubic foot (.45 cubic meter) rectangular chip basket with polyfiber sleeve
- Push-around configuration with two 4" x 2" swivel and two rigid casters
- Dimensions: 44" (1118 mm) long x 23.5" (597mm) wide x 51" (1295mm) high
- Weight: Approximately 350 pounds (159kg)
- Electrical: 120 volt, 60 Hz, 20 amp outlet (running amp draw is 14 amps)



Drum Top Air Sump Cleaner

The Drum Top Cleaner is an inexpensive vacuum device capable of vacuuming chips and solids from machine tools and work areas as well as emptying coolant sumps of liquids and solids. The unit is designed to be used on an open top 55 gallon drum.

Features

- Heavy duty drum cover plate
- Air venturi vacuum generator that mounts to cover plate
- Manual float switch to be used if unit will be used to vacuum liquids
- Fluid/solids deflector that mounts to underside of bottom plate
- 10' suction hose
- Hose to cover adapter
- 36" cleaning tool



Utility Requirements

Compressed air: 60-90 PSI, 32-47 CFM

Air hose: 1/2" ID unrestricted

Chip Basket Liners

Eriez' Sump Cleaners filter sludge and chips from cutting fluid via a reusable integral filter liner. The polypropylene filter sleeve filters to a nominal 50 microns. For finer filtration, a single use paper filter sleeve (to 20 microns nominal) can be inserted into the chip basket.



Eriez Sump Cleaners

| Capacity in gallons | Power | Length | Width | Height | Empty weight | Suction rate on water based fluids | Suction rating | Depth of pits able to vacuum fluid from | Discharge rate |
|------------------------|-------------------|--------|-------|--------|-----------------|--|-------------------|--|-------------------|
| 50 | 120 volt electric | 43" | 21.5" | 48.5" | 390 | 85 GPM | 9-10" Hg | 4' | 20-40 GPM |
| 50 | Air Venturi | 43" | 21.5" | 48.5" | 390 | 100 GPM | 13.5" Hg | 15' | 20-40 GPM |
| 100 | 120 volt electric | 84" | 34.5" | 62" | 975 | 85 GPM | 9-10" Hg | 4' | 20-40 GPM |
| 100 | Air Venturi | 84" | 34.5" | 62" | 975 | 100 GPM | 13.5" Hg | 15' | 20-40 GPM |
| 100 | 3 phase electric | 84" | 34.5" | 62" | 1200 | 100 GPM | 15" Hg | 15' | 20-40 GPM |
| 100 | LP gas | 84" | 34.5" | 62" | 1300 | 100 GPM | 15" Hg | 15' | 20-40 GPM |
| 175 | 120 volt electric | 79" | 36" | 68.5" | 1000 | 85 GPM | 9-10" Hg | 4' | 20-40 GPM |
| 175 | Air Venturi | 79" | 36" | 68.5" | 1000 | 100 GPM | 13.5" Hg | 15' | 20-40 GPM |
| 175 | 3 phase electric | 79" | 36" | 68.5" | 1225 | 100 GPM | 15" Hg | 15' | 20-40 GPM |
| 175 | LP gas | 79" | 36" | 68.5" | 1325 | 100 GPM | 15" Hg | 15' | 20-40 GPM |
| 275 | Air Venturi | 82" | 39.5" | 72" | 1125 | 100 GPM | 15" Hg | 15' | 20-40 GPM |
| 275 | 3 phase electric | 82" | 39.5" | 72" | 1350 | 100 GPM | 15" Hg | 15' | 20-40 GPM |
| 275 | LP gas | 82" | 39.5" | 72" | 1450 | 100 GPM | 15" Hg | 15' | 20-40 GPM |

Single compartment units larger than 275 gallons come with a tow package, forklift base, or for mounting on industrial trucks. These units are available in Air Venturi, 3 phase electric, and LP gas power in capacities of 300, 400, 500 and 1000 gallons.

Twin tank units are available in Air Venturi, 120 volt electric, 3 phase electric and LP gas power in capacities of 50/50, 100/100, 150/150, 200/200, 250/250, 300/300, 400/400 and 500/500 gallons.



WORLD AUTHORITY IN SEPARATION TECHNOLOGIES



WORLD HEADQUARTERS

2200 Asbury Road • Erie, PA 16506-1402 U.S.A.
P: 814-835-6000 • F: 814-838-4960
eriez@eriez.com • www.eriez.com



AUSTRALIA

Eriez Magnetics Pty. Ltd.
Epping, Victoria
P: +61 3 8401 7400



CHINA

Qinhuangdao and Tianjin
P: 86-22-8390-4608



PERÚ

Surco, Lima
P: 51 1 719 4150



BRAZIL

Belo Horizonte, Minas Gerais
P: 55 31 3281 9108



INDIA

Athipet, Chennai
P: 91-044-2652-5000



SOUTH AFRICA

Boksburg, Gauteng
P: 27-011-444-9160



CANADA

Eriez Flotation Division
Delta, British Columbia
P: +1 604-952-2300



JAPAN

Urayasu, Chiba
P: +81-47-354-6381



UNITED KINGDOM

Eriez Magnetics Europe Ltd
Bedwas, Caerphilly
P: 44-29-2086-8501



CHILE

Las Condes, Santiago
P: 56 2 29523400



MEXICO

Querétaro, Tlalnepantla
P: 52 555 321 9800



UNITED STATES

Asbury Rd | Wager Rd, Erie, Pennsylvania
P: 814-835-6000



Note: Some safety warning labels or guarding may have been removed before photographing this equipment.

Eriez and Eriez Magnetics are registered trademarks of Eriez Manufacturing Co., Erie, PA